

**FURUNO**



Total Control, Simply Refined

**NAVnet**

**TZ2**  
touch



[WWW.NAVNET.COM](http://WWW.NAVNET.COM)

# Total Control, Simply Refined

With a sleek all glass front, refined graphical user interface, built-in RezBoost™ Fish Finder, and internal GPS antenna, NavNet TZtouch2 is a beauty to behold and use.






## RezBoost™

NavNet TZtouch2 features a built-in Fish Finder that uses revolutionary new RezBoost™ technology.

>> [See page 13 for details](#)



## Instrument Display & Customization

An instrument display like nothing you have seen before. Totally customizable, totally simple.

>> [See page 6 for details](#)



## Refined User Interface

The User Interface has been completely reworked and refined, ensuring quick and easy operation.

>> [See pages 5-6 for details](#)



## Target Analyzer™ & Fast Target Tracking™ utilizing Doppler technology!

Target Tracking™ automatically show you hazardous targets by displaying them in bright red.

>> [See page 15 for details](#)




## iOS™ & Android™ Apps

View information from your NavNet TZtouch2 and control it on your iOS™ and Android™ devices.

>> [See page 7 for details](#)

## Simply refined, simply beautiful

Following in the footsteps of the original NavNet TZtouch, TZtouch2 features a refined user interface that is all about usability. Whether you are searching for hot fishing grounds, plotting your next route, using your Radar to navigate through the fog, you can expect smooth operation with familiar touch gestures. Sporting an edge-to-edge glass front, NavNet TZtouch2 is beautifully designed, allowing you to build a navigation suite that is not only functional, but offers a luxurious look and feel.



Model TZTL12F

### 12.1" Multi Function Display

Resolution: WXGA (1280 x 800 pixels)  
Brightness: 1300 cd/m<sup>2</sup> (typical)



Model TZTL15F

### 15.6" Multi Function Display

Resolution: FWXGA (1366 x 768 pixels)  
Brightness: 1100 cd/m<sup>2</sup> (typical)



## All-glass front, smooth to the touch



### **Bonded LCD - Clear Readability**

Our bonded LCDs offer a fog-free design that is used in both the TZTL12F and TZTL15F. This bonding ensures that the display is protected from condensation by sudden temperature changes. Optical bonding works by closing the air gap between the LCD and the cover glass, something that also enhances contrast.



### **Polarized Friendly - Clearly Remarkable**

NavNet TZtouch2 TZTL12F and TZTL15F have an LCD screen that does not "black out" when wearing polarized sunglasses. You are free to move around the vessel while maintaining clear visibility from virtually any angle.



### **Multi Touch Control**



With NavNet TZtouch, FURUNO introduced the industry's first multi touch MFD, and NavNet TZtouch2 is no disappointment. Improved touch control gives better response, as well as allowing you to swipe your fingers from the edge of the screen. Looking around your vessel in 3D, with the comprehensive charts available, Multi Touch Control makes navigating as simple as touch... and go!





### Quick Page

Swiping your finger down from the top edge of the screen displays the Quick Page. As the name implies, the Quick Page allows you to quickly change between the different screens from your current display. With bold colors, the previews are easy to differentiate and quickly choose from.



### Slide-Out Menu

The slide-out menu provides quick and easy access to often-used functions, and is available in every mode.



### Fully Customizable

Arrange instruments by the touch of your finger. You are free to customize the display to precisely fit your unique needs. Also note that instruments can overlap each other, giving you even more space to work with.



### Instruments

The instrument page is impressive just on its own rights, but where it really shines is its customizability. No matter if it is for navigation, engine and tank monitoring, autopilot control or all together, data can be displayed according to your personal tastes and needs.

# APPS

View information from your NavNet TZtouch2 and control it on your iOS™ and Android™ devices.



## NavNet Viewer App


Conveniently view instruments, as well as the fish finder of your NavNet TZtouch2 on your smart devices over a Wireless LAN network. Key navigational information such as Depth, Temperature, Wind, COG and Engine information can all be accessed from the palm of your hand. Even if you change the display on your NavNet TZtouch2, you can still view the fish finder on your smart devices.



## NavNet Controller App

Wirelessly control any NavNet TZtouch2 MFD with touch controls. With a scroll pad, cursor pad and dedicated keys within the app, controlling NavNet TZtouch2 is simple and straightforward.





# WIRELESS

## Marine Weather Forecast

The weather tool is completely free and easy to use, giving you unlimited access to weather forecasts worldwide 24 hours a day provided by NavCenter. Select the coverage you want, what type of data it is you need and for what time period, then it is simply a matter of choosing how to download the data. Navnet TZtouch2 can display up to 16 days of downloaded weather forecasting.



## ActiveCaptain\*, points of interest directly on your NavNet TZtouch2



NavNet TZtouch2, the world's first Multi Function Display with ActiveCaptain functionality. Share the experience together with other boaters around the world, browse and discover new points of interest. With a community of 250,000 users, reliable and updated information on fuel prices, marinas and obstructions are all available at the tip of your fingers. You can even rate and comment on points of interests, such as marinas and anchorages, straight from your NavNet TZtouch2.

\*Software version 3.01 or later is required.



## My TimeZero™ Cloud Data Service

My TimeZero cloud data service allows you to back up your data easily. Just connect your NavNet TZtouch2 to the internet and create a TimeZero account, and your settings, points\*, routes\* and tracks\* are automatically backed up to a remote server. You won't have to worry about losing your data ever again.

\*Coming soon

## Community Charts\*

Community Charts is a new layer of the MapMedia charts where users can update and modify chart information. Users can report changes such as chart depth, position of chart symbols, temporary obstructions, sunken ships, etc. which will get reviewed by MapMedia and shared among all the NavNet TZtouch2 users. Every time you connect your NavNet TZtouch2 to the internet you will automatically get the very latest chart information.

\*Coming soon

## BBWX3 – Sirius Satellite Weather Receiver\*

Keeping track of weather is easier than ever with Furuno's BBWX3 Third-Generation Sirius Satellite Weather Receiver! The weather information is obtained from the weather industry's leading experts and is delivered via digital receiver through Sirius' Marine Weather services. You can receive high-quality and comprehensive weather information and forecasting for use while navigating.




\*Satellite weather receiver service is available for all NavNet TZtouch2, TZtouch and NavNet 3D models. Requires Sirius weather service subscription, sold separately. Sirius weather coverage is currently available only in U.S and Canada.

# NavNet TZtouch2 Network



## RADAR



Radar Sensor  
**DRS4DL\*/DRS4D-NXT\***  
**DRS6A X-Class\***  
**DRS12A/DRS25A**

\*DRS4DL, DRS4D-NXT, DRS6A X-Class are ethernet only

## FISH FINDER\*1



Network Fish Finder  
**DFF1-UHD/DFF1/DFF3**

Bottom Discrimination Sounder  
**BBDS1**

## AIS



AIS Receiver  
**FA-30**



Class-B AIS Transponder  
**FA-50**



Class-A AIS Transponder  
**FA-170**

## WEATHER/ PC PLOTTER




MaxSea TIMEZERO  
 PC Software



Network Weather  
 Facsimile Receiver  
**FAX-30**



Network Satellite Weather  
 and Radio Receiver  
**BBWX3\*2**



## CAMERA/AUDIO



Marine Entertainment System  
**MS750 Series, etc.**



Analog Camera

## CONVERTER



NMEA Data Converter  
**IF-NMEA2K2**



Analog NMEA Data Converter  
**IF-NMEAFI**



Internal GPS Antenna



NavNet TZtouch2 is NMEA2000 certified. NMEA2000 offers improved data transfer rates and true plug-and-play operation.

\*1 External Fish Finders can also be connected to NavNet TZtouch2. The internal and external Fish Finder cannot operate simultaneously. Through the settings menu it is possible to choose which one to use.

\*2 Sirius weather coverage is currently available only in U.S and Canada. Sirius subscription required.

\*3 External GPS antennas and navigators can also be connected to NavNet TZtouch2. Through the settings menu it is possible to choose which one to use.

# Perfect match!

NavNet TZtouch2, NAVpilot-711C and the FI-70 have been designed to match each other beautifully, both in appearance and in function. Sporting a clean and functional design in all black, they will make a great addition to your helm.



NavNet TZtouch2



NAVpilot-711C



FI-70



NAVpilot-700

CAN bus NMEA0183



NAVpilot-711C

CAN bus NMEA0183

## AUTOPILOT



Satellite Compass  
SC-30

CAN bus



Integrated Heading Sensor  
PG-700

CAN bus

## COMPASS



GPS/WAAS  
Receiver Antenna  
GP-330B

CAN bus



GPS Navigator  
GP-33

CAN bus

## GPS\*3



Depth/Speed/Temp Sensor  
DST-800

CAN bus

## SENSOR



Internal Fish Finder  
with RezBoost™ technology

NEW



Remote Control Unit  
MCU-004

USB



Remote Control Unit  
MCU-002

USB



FI-70

CAN bus

## INSTRUMENT



SD Card Unit  
SDU-001

USB

## OPTION

# Nothing Is Faster Than TimeZero™

NavNet TZtouch2's TimeZero™ technology delivers chart processing like you've never seen before – seamless chart handling, zooming and panning without the screen disappearing. TimeZero™ technology redefines the meaning of stress-free operation by smoothing out your chart handling actions.



## The Only Acceptable Wait Time is Zero:

### TimeZero™ Technology Changes Your Perspective on Chart Redraw

Equipped with powerful TimeZero™ technology, NavNet TZtouch2 will completely transform the way you navigate. You can scroll, pan, zoom in/out with a smooth, fast and seamless graphics engine. Navigating in a 3D environment offers you a true perspective and wider area of view around the ship, which allows you to better plan your routes. TimeZero™ technology updates the information on your screen with virtually no redraw as you go.



# Chart Plotter

## Mapmedia Vector and Raster Chart Library

With NavNet TZtouch2 it's possible to freely choose the charts that fit your individual needs. With the optional NOAA raster and vector charts, Mapmedia brings an authentic vector and raster chart library to your NavNet TZtouch2. "C-MAP by Jeppesen" as well as "Datacore by Navionics" vector cartography are optional charts that can be downloaded to your TZtouch2 with ease. Mapmedia cartography integrates cutting edge algorithms with high resolution image processing techniques to deliver a fusion of digital navigation charts and satellite photography.



2D Raster

2D Vector

## Satellite PhotoFusion™

Satellite photography is included in the Mapmedia Raster and Vector charts, simply called Satellite PhotoFusion™. Land areas (zero depth) are completely opaque, displayed as satellite photos on the chart. As the depth increases, the satellite image is merged with the chart data to provide you with added detail on seabed areas in shallow water, without losing vital chart information. In deeper water, where the satellite photos have no detail to offer, the chart is displayed without alteration.



Raster+Satellite

Vector+Satellite


## Depth Shading

A depth color scale can be applied to both 2D and 3D vector and raster charts. Transparency levels can be adjusted so that chart data is visible beneath the color shading. This unique feature allows you to view water depths at-a-glance with vibrant colors. No more searching for depth numbers, when you can simply set depths to your specified colors. Whether you want to see the depth for navigation or fishing purposes, this feature makes it easier than ever before.



## AIS Target Tracking

When connecting a FURUNO FA-30/50/150 AIS unit to your NavNet TZtouch2, up to 100 AIS targets can be tracked and displayed on the Chart Plotter screen. The Automatic Identification System (AIS) improves safety during travel by sharing the status and position of your vessel with other AIS-equipped vessels nearby. You can easily read detailed information about AIS-equipped vessels nearby such as speed, heading, Closest Point of Approach and Time to Closest Point of Approach.



## Fish Finder


NavNet TZtouch2 is the first product from FURUNO to feature the brand new RezBoost™ technology. Accurately spot individual fish and increase your catch.




Up to 8 times  
sharper image than  
conventional FDF\*1

### RezBoost™

Rezboost™ is a revolutionary new technology utilizing FURUNO's advanced digital signal processing to provide fantastic resolution without having to change your transducer.



Conventional Signal Processing



RezBoost™ Signal Processing

RezBoost™ improves target separation close to the seabed, as well as giving an unprecedented boost in resolution. With RezBoost™ technology, resolution and target separation previously limited to FURUNO commercial-grade Fish Finders can now be achieved. RezBoost™ technology makes it easier to spot individual fish in tightly packed fish schools, as well as discerning game fish from bait fish. Since RezBoost™ technology is software based, you can use transducers\* already installed on your vessel.

\* To check if your transducer supports the "Enhanced Mode", see FURUNO.com for further information.  
In-hull mounted transducers not compatible with RezBoost™ technology.

\*1 RezBoost™ performance may vary depending on depth, range and signal frequency used.



### FURUNO Digital Filter (FDF™) Fish Finder


FURUNO Digital Filter (FDF™) fish finders feature advanced filtering capabilities and digital auto tuning, which eliminates noise. FURUNO FDF™ fish finders deliver the ability to spot individual fish with clarity, accuracy and detail. Whether in shallow or deep water, FURUNO FDF™ fish finders give you what you would expect from a fish finder at all times.




Up to 10 times sharper image than conventional FDF\*2

## Find More Fish With TruEcho CHIRP™ Fish Finder

An advanced technology for both professional and enthusiast fishermen. Designed to operate across a wide range of frequencies utilizing a broadband transducer, the TruEcho CHIRP™ network fish finder delivers significant advantages in signal clarity and target definition. Due to the constant sweep of frequencies the TruEcho CHIRP™ network fish finder is capable of gathering more and higher quality data than a traditional single frequency fish finder. The clear presentation marks individual game fish and bait fish, even when tightly schooled together.




High Frequency CHIRP



Low Frequency CHIRP

\*2 TruEcho CHIRP™ performance may vary depending on depth, range and signal frequency used.

## ACCU-FISH



### ACCU-FISH™ (Fish Size Analyzer)


The ACCU-FISH™ algorithm analyzes echo returns in order to compute individual fish size. The algorithm is capable of computing fish size ranging from 10 cm up to 199 cm long. Fish depth can also be displayed.

*In some instances, fish size indicated on the NavNet TZtouch2 may differ from its actual size. Please carefully read the operator's manual prior to utilizing this feature.*



### Bottom Discrimination Display

Bottom discrimination provides detailed information about Knowing the make-up of the seabed, categorizing it into four different categories; "Rocks", "Gravel", "Sand" and "Mud". The make-up of the seabed can be tremendously helpful information when looking for fishing grounds, as well as for finding good anchoring spots.



BLACK BOX NETWORK FISH FINDER



BLACK BOX NETWORK FISH FINDER

	Internal Fish Finder	DFF1-UHD	DFF3
Frequency	Dual frequency 50kHz and 200 kHz	Dual frequency 50±20 and 200±25 kHz	The synthesized transducer works with dual frequencies between 28 and 200 kHz
Range Scale	Up to 1,200 m		
Transducers	600 W or 1 kW*	1 kW	Up to 3,000 m 1, 2 or 3 kW
ACCU-FISH™	Available**		
Bottom Discrimination	Available		N/A
TruEcho CHIRP™	N/A	Available	N/A
RezBoost™	Available	N/A	

DFF1/BBDS1 are fully compatible with NavNet TZtouch2.

\*Matching Box MB-1100 required for some specific FURUNO transducers.

\*\* For DFF3, with 50/200-1T transducer only.

# Radar



Model DRS25A

Model DRS12A

Model DRS6A X-Class

Model DRS4DL

## Radar Sensors



Winner of the NMEA awards  
2008, 2009, 2010, 2011,  
2012, 2013 and 2014



Model DRS4D-NXT



Exclusive DRS4D-NXT features

### DRS4D-NXT, the NXT step in Radar technology

Solid-State Radar with pulse compression, Target Analyzer™ and Fast Target Tracking™ utilizing Doppler technology. Combined with FURUNO exclusive RezBoost™ technology for beam sharpening, DRS4D-NXT packs the performance of an open array radar, in a compact 24" radome. Target Tracking™ automatically show you hazardous targets by displaying them in bright red. Stationary targets are displayed in green.

\* System version 3.01 or later is required.

### New Target Analyzer™ function\*



With Target Analyzer™, hazardous targets are displayed in red


### DRS6A X-Class, a whole new class of Radar

Pushing the boundaries of what is possible with conventional Radar technology, DRS6A X-Class marks yet another leap forward for FURUNO. Improved in almost all aspects, DRS6A X-Class Radar features improved short range detection as well as an impressive long range detection of up to 120 nautical miles. And that's not all, the new "Bird Mode" gives you incredible bird detection performance.

\*1 System version 3.01 or later is required.

\*2 Bird mode is also available with DRS4D-NXT, and DRS2D/4D/4A/6A/12A/25A (upcoming v1.18 software needed).

### New Bird Mode\*




Bird echoes, to the right of the screen

## ARPA Target Tracking


With ARPA Target Tracking enabled, up to 30\* different targets can be tracked simultaneously. Targets can be acquired either manually or fully automatically. Automatic Radar Plotting Aid (ARPA) calculates the tracked objects course and speed, as well as the CPA (Closest Point of Approach). With this information, the Radar is capable of predicting possible collision courses and sound relevant alarms. In combination with AIS, this spells increased security and ease of mind on your vessel.

\*100 different targets for DRS4D-NXT, not available on DRS4DL



## Real-Time Digital Auto Gain/Sea Controls

NavNet TZtouch2 employs revolutionary real-time digital auto Gain/Sea controls to deliver a crystal clear radar presentation. With this new technology, NavNet TZtouch2 computes and applies an adaptive omni-directional anti-clutter filter with variable intensity according to vessel bearing. With the use of this technology, automatic gain and sea clutter have achieved such a high level of proficiency that one rarely needs to venture into the manual modes. Set the Radar to auto and focus on more important things at hand.




Auto Gain/Sea Controls On    Auto Gain/Sea Controls Off

## Simultaneous Dual Range Radar Scanning

Simultaneous scanning technology sends out a dual progressive scan that is processed and presented on the NavNet TZtouch2. This technology allows for two different radar ranges to be displayed simultaneously, each range with autonomous control over gain and anti-clutter settings. One of the many things that can be done with dual range scanning is, for example, to set one range for bird detection and the other for navigation.

Not available on DRS4DL, Limited to 12 nm on DRS4D-NXT



## AIS Target Tracking

When connecting a FURUNO FA-30/50/150 AIS unit to the NavNet TZtouch2, up to 100 AIS targets can be tracked and displayed on the Radar screen. The Automatic Identification System (AIS) improves safety during travel by sharing the status and position of your vessel with other AIS-equipped vessels nearby. You can easily read detailed information about AIS-equipped vessels nearby such as speed, heading, Closest Point of Approach and Time to Closest Point of Approach.



## NavNet TZtouch2 Radar Sensor Options

	DRS4DL	DRS4D-NXT <span style="color: orange;">NEW</span>	DRS6A X-Class <span style="color: orange;">NEW</span>	DRS12A	DRS25A
Output Power	4 kW	Solid-state, 25 W	6 kW	12 kW	25 kW
Size	19 inch	24 inch	3.5 ft/4 ft/6 ft	4 ft/6 ft	4 ft/6 ft
Antenna Type	Radome	Radome	Open	Open	Open
Beam Width	Horizontal	5.2°	2.3°/1.9°/1.4°	1.9°/1.4°	1.9°/1.4°
	Vertical	25°	25°	22°/22°	22°/22°
Max. Range	36 nm	36 nm	120 nm	120 nm	120 nm
48 rpm Capability	—	•	•	•	•
Power Amp Unit required	—	—	—	PSU-012	PSU-013
Functions	Head-up, North-up*	Head-up, North-up*, Fast Target Tracking, Target Analyser, Bird Mode	Head-up, North-up*, Fast Target Tracking, Bird Mode	Head-up, North-up*, Target Tracking	Head-up, North-up*, Target Tracking
Dual Range Scanning	—	• (Range is limited to 12 nm)	•	•	•
ARPA	—	•	•	•	•

\* Heading input required.

The radar antenna complies with IEC62252 Ed.1:2004 (Clauses 4.33, 5.33, Annex D) relevant to radio characteristic.

# Specifications

Model **TZTL12F**




Bracket is optional supply.

MULTI FUNCTION DISPLAY		TZTL12F	
<b>DISPLAY UNIT</b>			
Type	Color TFT multi touch LCD		
Screen Size	12.1" Wide		
Screen Resolution	WXGA 1280 x 800		
Screen Brightness	1300 cd/m <sup>2</sup> (typical)		
Language	English (US & UK), French, Spanish, German, Italian, Dutch, Turkish, Portuguese, Swedish, Danish, Norwegian, Finnish, Greek, Russian, Chinese (simplified Chinese characters), Japanese		
<b>GPS/WAAS</b>			
Receiver Type	GPS	56 channels	
	SBAS	1 channel (C/A mode, WAAS)	
Receiving Frequency	L1 (1575.42 MHz)		
Time to First FIX	100 s (cold start)		
Tracking Velocity	999 kn		
SBAS	WAAS, EGNOS, MSAS		
<b>ACCURACY</b>			
Internal Antenna	GPS	10 m Max	
	WAAS	3 m Max	
	MSAS	7 m Max	
<b>CHART PLOTTER</b>			
Cartography	MapMedia mm3d chart (Jeppesen/Navionics/NOAA)		
Memory Capacity	30,000 user points, 30,000 points for ship's tracks, 200 planned routes (500 points per route)		
Alarms	Anchor Watch, XTE, Proximity, Depth, Temperature, Speed, etc.		
<b>RADAR</b>			
Display Modes	Head-up, North-up* *Heading input required.		
Target Tracking**	30 Targets* *Heading input required.		
<b>FISH FINDER (Built-in)</b>			
Transmit Frequency	50/200 kHz		
Transmission Power	600 W or 1 kW* *Matching Box MB-1100 required for some specific FURUNO transducers		
Modes	RezBoost™, ACCU-FISH™, Bottom Discrimination, A-Scope, Auto (Fishing/Cruising/Manual), Bottom Zoom, Bottom Lock		
<b>INTERFACE</b>			
CAN bus/NMEA2000	1 Port		
Interface (CAN bus/NMEA2000)	Input	059392, 059904, 061184, 060928, 065280, 126208, 126720, 126992/996, 127237/245/250/251/257/258/488/489/505, 128259/267, 129025/026/029/033/038/039/040/041/291/538/540, 129793/794/798/808/809/810, 130306/310/311/312/313/314/316/577/578/817/818/820/822/823/826/827/828/880	
	Output	059392, 059904, 061184, 060928, 126208/464/720/992/996, 127250/251/257/258, 128259/267, 129025/026/029/033/283/284/285, 130306/310/312/313/314/316/821/822/823/827	
NMEA0183	1 Integrated Output Port		
Interface (NMEA0183)	Output	AAM, APB, BOD, GGA, GLL, GNS, GSA, GSV, RMB, RTE, TLL, TTM, VTG, WPL, XTE, ZDA	
LAN	1 Port (100BASE-TX)		
USB	1 Port (USB2.0)		
Video Output	1 Port (HDMI)		
Video Input	2 Ports (NTSC/PAL)		
AUX I/O	1 Port (External Event/MOB Input/Operator Fitness/Alarm Output)		
SD Card Slot	1 Slot (Micro SDXC, rear), 2 Slots Card Unit (optional)		
Wireless LAN	IEEE802.11b/g/n, Transmit frequency: 2.4 GHz band		
Transducer	1 Port		
<b>ENVIRONMENT</b>			
Temperature (IEC60945)	-15°C to +55°C		
Waterproofing	IP56		
<b>POWER</b>			
	12-24 VDC		
	3.0-1.5 A		


\*\* Not available with DRS4DL

Multi Function Display (Tabletop Mount) TZTL12F  
3.8 kg 8.4 lb



Bracket is optional supply.

Multi Function Display (Flush Mount) TZTL12F  
3.7 kg 8.2 lb



Model **TZTL15F**




Bracket is optional supply.

MULTI FUNCTION DISPLAY		TZTL15F	
<b>DISPLAY UNIT</b>			
Type	Color TFT multi touch LCD		
Screen Size	15.6" Wide		
Screen Resolution	FWXGA 1366 x 768		
Screen Brightness	1100 cd/m <sup>2</sup> (typical)		
Language	English (US & UK), French, Spanish, German, Italian, Dutch, Turkish, Portuguese, Swedish, Danish, Norwegian, Finnish, Greek, Russian, Chinese (simplified Chinese characters), Japanese		
<b>GPS/WAAS</b>			
Receiver Type	GPS	56 channels	
	SBAS	1 channel (C/A mode, WAAS)	
Receiving Frequency	L1 (1575.42 MHz)		
Time to First FIX	100 s (cold start)		
Tracking Velocity	999 kn		
SBAS	WAAS, EGNOS, MSAS		
<b>ACCURACY</b>			
Internal Antenna	GPS	10 m Max	
	WAAS	3 m Max	
	MSAS	7 m Max	
<b>CHART PLOTTER</b>			
Cartography	MapMedia mm3d chart (Jeppesen/Navionics/NOAA)		
Memory Capacity	30,000 user points, 30,000 points for ship's tracks, 200 planned routes (500 points per route)		
Alarms	Anchor Watch, XTE, Proximity, Depth, Temperature, Speed, etc.		
<b>RADAR</b>			
Display Modes	Head-up, North-up* *Heading input required.		
Target Tracking**	30 Targets* *Heading input required.		
<b>FISH FINDER (Built-in)</b>			
Transmit Frequency	50/200 kHz		
Transmission Power	600 W or 1 kW* *Matching Box MB-1100 required for some specific FURUNO transducers		
Modes	RezBoost™, ACCU-FISH™, Bottom Discrimination, A-Scope, Auto (Fishing/Cruising/Manual), Bottom Zoom, Bottom Lock		
<b>INTERFACE</b>			
CAN bus/NMEA2000	1 Port		
Interface (CAN bus/NMEA2000)	Input	059392, 059904, 061184, 060928, 065280, 126208, 126720, 126992/996, 127237/245/250/251/257/258/488/489/505, 128259/267, 129025/026/029/033/038/039/040/041/291/538/540, 129793/794/798/808/809/810, 130306/310/311/312/313/314/316/577/578/817/818/820/822/823/826/827/828/880	
	Output	059392, 059904, 061184, 060928, 126208/464/720/992/996, 127250/251/257/258, 128259/267, 129025/026/029/033/283/284/285, 130306/310/312/313/314/316/821/822/823/827	
NMEA0183	1 Integrated Output Port		
Interface (NMEA0183)	Output	AAM, APB, BOD, GGA, GLL, GNS, GSA, GSV, RMB, RTE, TLL, TTM, VTG, WPL, XTE, ZDA	
LAN	1 Port (100BASE-TX)		
USB	1 Port (USB2.0)		
Video Output	1 Port (HDMI)		
Video Input	2 Ports (NTSC/PAL)		
AUX I/O	1 Port (External Event/MOB Input/Operator Fitness/Alarm Output)		
SD Card Slot	1 Slot (Micro SDXC, rear), 2 Slots Card Unit (optional)		
Wireless LAN	IEEE802.11b/g/n, Transmit frequency: 2.4 GHz band		
Transducer	1 Port		
<b>ENVIRONMENT</b>			
Temperature (IEC60945)	-15°C to +55°C		
Waterproofing	IP56		
<b>POWER</b>			
	12-24 VDC		
	3.6-1.8 A		


\*\* Not available with DRS4DL

Multi Function Display (Tabletop Mount) TZTL15F  
5.5 kg 12.1 lb



Bracket is optional supply.

Multi Function Display (Flush Mount) TZTL15F  
4.8 kg 10.6 lb





[www.furuno.com](http://www.furuno.com)

Beware of similar products

All brand and product names are registered trademarks, trademarks or service marks of their respective holders.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

**FURUNO ELECTRIC CO., LTD.**

Nishinomiya, Hyogo, Japan  
[www.furuno.com](http://www.furuno.com)

**FURUNO U.S.A., INC.**

Camas, Washington, U.S.A.  
[www.furunousa.com](http://www.furunousa.com)

**FURUNO (UK) LIMITED**

Havant, Hampshire, U.K.  
[www.furuno.co.uk](http://www.furuno.co.uk)

**FURUNO FRANCE S.A.S.**

Bordeaux-Mérignac, France  
[www.furuno.fr](http://www.furuno.fr)

**FURUNO ITALIA S.R.L.**

Gatteo Mare, Italy  
[www.furuno.it](http://www.furuno.it)

**FURUNO ESPAÑA S.A.**

Madrid, Spain  
[www.furuno.es](http://www.furuno.es)

**FURUNO DANMARK A/S**

Hvidovre, Denmark  
[www.furuno.dk](http://www.furuno.dk)

**FURUNO NORGE A/S**

Ålesund, Norway  
[www.furuno.no](http://www.furuno.no)

**FURUNO SVERIGE AB**

Västra Frölunda, Sweden  
[www.furuno.se](http://www.furuno.se)

**FURUNO FINLAND OY**

Espoo, Finland  
[www.furuno.fi](http://www.furuno.fi)

**FURUNO POLSKA Sp. Z o.o.**

Gdynia, Poland  
[www.furuno.pl](http://www.furuno.pl)

**FURUNO EURUS LLC**

St. Petersburg, Russian Federation  
[www.furuno.com.ru](http://www.furuno.com.ru)

**FURUNO SINGAPORE PTE LTD**

Singapore  
[www.furuno.sg](http://www.furuno.sg)

**FURUNO DEUTSCHLAND GmbH**

Pellingen, Germany  
[www.furuno.de](http://www.furuno.de)

**FURUNO HELLAS S.A.**

Piraeus, Greece  
[www.furuno.gr](http://www.furuno.gr)

**FURUNO (CYPRUS) LTD**

Limassol, Cyprus  
[www.furuno.com.cy](http://www.furuno.com.cy)

**FURUNO CHINA CO., LTD.**

Hong Kong  
[www.furuno.com/cn](http://www.furuno.com/cn)

**FURUNO SHANGHAI CO., LTD.**

Shanghai, China  
[www.furuno.com/cn](http://www.furuno.com/cn)

1605PDF Printed in Japan  
Catalogue No. R-207e