


Note:


1. Waterproof Rate: IP67
(No Ingress Of Dust/ Protected Against Harmful Effects Caused In 1 Meter Water Within 30 Minutes)
2. Temperature Range: -20°C to +80°C
3. Current Rating: 3A
4. Material:
Housing: Nylon, Black
Pin: Copper Alloy, 30u" Gold Plated
Screw Nut: Brass, Nickel Plated

5. Cable: (24AWG*1P+AL/MY)+(22AWG*1P+AL/MY)+D+B, CL2 ,PVC Jacket, Black, OD=ø6.7mm
6. Cable Length Limit: 20M Or 66ft
7. Part No.: NAP-MM1MF1000GXXX
8. Cable Length Tolerance:

01M: L=1M	01F: L=1ft
L±10%mm<50cm	02F: L=2ft
	:
50cm≤L±40mm<1M	20F: L=20ft
	:
1M≤L±5%<10M	66F: L=66ft
	:
10M≤L±500mm	
9. Unit Conversion: 1M=3.28ft, 1ft=0.3048M





Conn.1
Pin Assignments Front View



Conn.2
Pin Assignments Front View

5	Blue (24AWG) 藍	5	Twist
4	White (24AWG) 白	4	
3	Black (22AWG) 黑	3	Twist
2	Red (22AWG) 紅	2	
1	Drain (22AWG) 地線	1	
Conn.1	Wire Color	Conn.2	
Pin Out			

 歐德斯電通科技股份有限公司					
TITLE					
NMEA,MICRO,T-CABLE					
QC : QC check		DSGN. Reg	PART NO. NAP-MM1MF1000GXXX		
TOLERANCE ±0.50		SCALE 1 : 1	DWN. Nancy	DATE 2016/01/18	
	UNIT: mm	SIZE A4	CHKD. Miller	DATE 2016/01/18	
	SHEET 1 of 1	REV. A	APVD. Reg	DATE 2016/01/18	