





REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2016/01/18	Nancy	Change Rev 02 To Issue Rev A



Conn.




M12*1.0



Pin Assignments
Front View

5	Blue (24AWG)	藍	Twist
4	White (24AWG)	白	
3	Black (22AWG)	黑	Twist
2	Red (22AWG)	紅	
1	Drain (22AWG)	地線	
Conn.	Wire Color		
Pin Out			



Note:

- Waterproof Rate: IP67
(No Ingress Of Dust/ Protected Against Harmful Effects Caused In 1 Meter Water Within 30 Minutes)
- Temperature Range: -20°C to +80°C
- Current Rating: 3A
- Material:
Housing: Nylon, Black
Pin: Copper Alloy, 30u" Gold Plated
Screw Nut: Brass, Nickel Plated
- Cable:
(24AWG*1P+AL/MY)+(22AWG*1P+AL/MY)+D+B,
CL2 ,PVC Jacket, Black, OD=Ø6.7mm
- Cable Length Limit: 20M Or 66ft
- Part No.: NAMBM05MCC-SLC7GXXX
- Cable Length Tolerance:

01M: L=1M	01F: L=1ft
L±10%mm<50cm	02M: L=2M
50cm≤L±40mm<1M	02F: L=2ft
1M≤L±5%<10M	20M: L=20M
10M≤L±500mm	20F: L=20ft
	66F: L=66ft
- Unit Conversion: 1M=3.28ft, 1ft=0.3048M

ODS 歐德斯電通科技股份有限公司				
TITLE				
NMEA,MICRO-C,CABLE MM				
QC	QC check	DSGN	Reg	PART NO. NAMBM05MCC-SLC7GXXX
TOLERANCE	±0.50	SCALE	1 : 1	DWN. Nancy
UNIT	mm	SIZE	A4	CHKD. Miller
SHEET	1 of 1	REV.	A	APVD. Reg
		DATE		2016/01/18
		DATE		2016/01/18
		DATE		2016/01/18