




REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2016/01/18	Nancy	Change Rev 03 To Issue Rev A




Note:


- Waterproof Rate: IP68
(No Ingress of Dust/ Protected Against Harmful Effects
Caused In 1 Meter Water Within 24 Hours)
- Temperature Range: -40°C to +105°C
- Current Rating: 5A
- Max. Panel Thickness 16mm (Without Cap Chain)
- Material:
Housing: Nylon, Black
Pin: Copper Alloy, 30u" Gold Plated
Screw Nut: Brass, Nickel Plated



Conn.1
Pin Assignments Front View



Conn.2
Pin Assignments Front View



Recommended Panel Cut-Out

<div> 歐德斯電通科技股份有限公司 </div>				
TITLE NMEA,MICRO-C,BULKHEAD				
QC : QC check		DSGN Reg	PART NO. NMH-MM1MF1000001	
TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1°	 UNIT: mm SHEET 1 of 1	SCALE 1 : 1 SIZE A4 REV. A	DWN. Nancy CHKD. Miller APVD. Reg	DATE 2016/01/18 DATE 2016/01/18 DATE 2016/01/18