



REV. A	ECN NO.	DATE 2016/01/18	SIGN Nancy	DESCRIPTION Change Rev 02 To Issue Rev A




Note:

1. Waterproof Rate: IP67  
(No Ingress Of Dust/ Protected Against Harmful Effects Caused In 1 Meter Water Within 30 Minutes)
2. Temperature Range: -20°C to +80°C
3. Current Rating: 3A
4. Material:  
Housing: Nylon, Black  
Pin: Copper Alloy, 30u" Gold Plated  
Screw Nut: Brass, Nickel Plated

5. Cable:  
(24AWG\*1P+AL/MY)+(22AWG\*1P+AL/MY)+D+B,  
CL2 ,PVC Jacket, Black, OD=6.7mm
6. Cable Length Limit: 20M Or 66ft
7. Part No.: NAD-MM1MF1000GXXX
8. Cable Lenght Tolerance:
 

01M: L=1M	01F: L=1ft
L±15%mm<50cm	02M: L=2M
50cm≤L±60mm<1M	20M: L=20M
1M≤L±5%<10M	20F: L=20ft
10M≤L±500mm	66F: L=66ft
9. Unit Conversion: 1M=3.28ft, 1ft=0.3048M



5	Blue	(24AWG)	藍	5	Twist
4	White	(24AWG)	白	4	
3	Black	(22AWG)	黑	3	Twist
2	Red	(22AWG)	紅	2	
1	Drain	(22AWG)	地線	1	
Conn.1	Wire Color			Conn.2	
Pin Out					

<div>ODS 歐德斯電通科技股份有限公司</div>				
TITLE NMEA,MICRO-C,DOUBLE END CABLE				
QC : QC check		DSGN Reg	PART NO. NAD-MM1MF1000GXXX	
TOLERANCE ±0.50	UNIT: mm	SCALE 1 : 1	DWN. Nancy	DATE 2016/01/18
SHEET 1 of 1	REV. A	CHKD. Miller	DATE 2016/01/18	
		APVD. Reg	DATE 2016/01/18	